



TECHNICAL PAINT SERVICES

A1006 PROTEKT IT! PAINT

Features:

A rust-beating self priming, single coat paint designed to give maximum protection to all ferrous metals with a minimum of preparation. Ideal for use on farm buildings, trailers, railings, drain covers, metal groundwork, inside gutters & drains, and structural steel. Protects for up to 5 years.

Availability:

5, 2.5, and 1 Litre containers in neutral Battle Ship Grey. Other colours available to order in a minimum of 25 Litres.

Volume Solids:

60% + 3% (BS 3900 Part A10).

Preparation:

The substrate should be degreased as necessary. Remove any loose rust with a wire brush or coarse sandpaper and clean with UTR112 Thinners and allow time to dry. Apply Protekt It! directly onto the rusty metal surface with a minimum drying temperature of 6°C. Avoid application in damp or wet conditions. No need for primer or undercoat. Not suitable for sustained periods of immersion.

Coverage:

Approximately 30 - 35 sq meters per 5 Litres with one heavy brush coat.

Drying:

Touch dry: 30 minutes.

Fully cured: 24 hours.

Do not recoat as only one coat is required.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.