



# TECHNICAL PAINT SERVICES

## A147 SQUASH COURT EGGSHELL FINISH

**Features:**

A tough, durable finish suitable for Squash Courts. Not to be used over armour coat polished plaster or coatings.

**Availability:**

All BS4800 colours plus Black and White in 5, 2.5 and 1 Litre containers.

**Volume Solids:**

55% ± 3% (BS 3900 Part A10).

**Preparation:**

The substrate must be thoroughly clean, dry and free from dust and grease. Apply over AS147/5/4 Squash Court Acrylic Sealer White.

**Application:**

Brush, roller, conventional or airless spray. Supplied ready for use for brushing. Thin up to 25% by volume using UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 40 seconds BSB4 cup @ 20°C. Apply two coats allowing overnight drying between coats.

**Coverage:**

Approximately 40 sq metres per 5 Litres.

**Drying:**

Touch dry: 20 - 30 minutes @ 20°C.

Hard dry: Overnight.

Optimum hardness: 7 days.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.