



TECHNICAL PAINT SERVICES

A48 AMEL LEAD BASED FINISHES

Features:

A lead based decorative paint, which exhibits excellent exterior durability, especially when applied over lead based primers or undercoats suitable for wood or metal. Only to be used on approved surfaces. Lead Regulations apply. In case of any queries, please contact our Technical Department prior to purchase.

Availability:

BS4800 colour range in 5 Litre containers, to order only.

Volume Solids:

65% ± 3% (BS 3900 Part A10) - may vary with colour.

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Brush only. Supplied ready for use. Use X156 White Spirit for cleaning.

Coverage:

Approximately 60 sq metres per 5 Litres depending on porosity of the substrate.

Drying:

Touch dry: Up to 12 hours @ 20°C.

Minimum over coating time: 48 hours.

Maximum over coating time: 1 month.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 0845 230 1244 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.com

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.