



TECHNICAL PAINT SERVICES

AL32/70/1 FLOOR FINISH PHENOLIC TUNG CLEAR

Features:

A pure phenolic wood oil varnish, affording excellent water and mild chemical resistance. Ideally suited for application to all wooden floors. This paint should not be applied over PVA sealer, latex self leveling compound or power floated concrete. Please contact our Technical Department.

Availability:

All BS4800 colours in 5, 2.5 and 1 Litre containers.
AL33/70/1 Floor Finish Phenolic Tung Non-Slip is also available.

Volume Solids:

53% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease.

Application:

By brush, roller or squeegee. On unvarnished wood (including worn surfaces), apply an initial sealer coat thinned up to 20% with X156 White Spirit, followed by two un-thinned coats. If coats are applied at 24 hour intervals, it is not necessary to rub down between coats.

Coverage:

60 sq metres per 5 Litres.

Drying:

Touch dry:	4 hours @ 20°C.
Hard dry:	8 hours.
Recoatable:	Overnight.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.