



TECHNICAL PAINT SERVICES

AS147/5/4 SQUASH COURT ACRYLIC SEALER WHITE

Features:

This water-based 100% pure acrylic sealer is suitable for all types of substrate. Ideal for sealing plastered walls as a base for A147 Squash Court Eggshell Finish, White or Colours.

Availability:

In 5, 2.5 and 1 Litre containers.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Plaster must be at least 3 months old, and any imperfect surfaces must be made good before application of AS147/5/4.

Application:

Brush, roller, conventional or airless spray. For optimum results, AS147/5/4 should be thinned approximately 25% with clean tap water to aid penetration of porous surfaces. It is recommended that two coats are applied to previously un-treated porous surfaces, allowing 2 hours drying between coats.

Coverage:

Approximately 50 sq metres per 5 Litres depending on the porosity of the substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.