



TECHNICAL PAINT SERVICES

E26 VINYL EMULSION

Features:

A decorative finish available in matt or silk with excellent exterior durability, good opacity and washability. Suitable for application to plaster, brickwork, concrete, chipboard, paper, asbestos and plasterboard. Also made in EG26 Contract Grade.

Availability:

BS4800 colour range in 5, 2.5 and 1 Litre containers. Trade and Contract qualities are available in a limited range of colours.

Volume Solids:

34% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean and free from oil, dust and grease.

Application:

Brush, roller or spray. Supplied ready for use for brushing. Use clean tap water for thinning, if required and cleaning. When applying to new untreated surfaces, it is recommended that a first coat should be applied thinned up to 20% with clean water.

Coverage:

Approximately 50 - 60 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 2 hours @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.