



TECHNICAL PAINT SERVICES

E4 WATER BASED ANTI-CONDENSATION PAINT SMOOTH

Features:

A water-borne paint which provides a thick, matt, granular yet smooth coating for interior surfaces. Reduces condensation by insulating the substrate and absorbing an amount of condensed water. Prevents unsightly staining due to condensation runs.

Availability:

5 Litre containers in White and Pastel colours only.

Volume Solids:

30 % + 3% (BS 3900 Part A10).

Preparation:

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel, remove all millscale and rust. Prime bare surfaces with AP79 Primer and areas of damp plaster or brickwork with EP26 Primer. Lightly abrade glossy areas with fine waterproof abrasive paper.

Application:

Stir well before use. Suitable for brush or conventional spray. Apply two full coats and allow 2 to 3 hours between coats under normal conditions. Do not apply when air or surface temperature is below 10°C. Brush marks can be camouflaged by stippling. On wall areas likely to be touched or leant against, the application of a protective coat of ES27/70 Acrylic Sealer Clear over the dry film of E4 Anti-Condensation Paint Smooth is recommended.

Coverage:

Approximately 5 sq metres per Litre, depending on the nature and the porosity of the surface being painted.

Drying:

Touch dry:	1 - 2 hours @ 20°C.
Recoatable:	2 - 3 hours @ 20°C.
Fully cured:	6 - 8 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.