



TECHNICAL PAINT SERVICES

E57 IMITATION STONE WATER BASED

Features:

A durable, weather resistant, water based finish with an attractive granular texture, suitable for application to cement rendering, concrete, brickwork and interior walls and ceilings where plasterwork is of poor quality.

Availability:

All BS4800 colours in 5, 2.5 and 1 Litre containers.

Volume Solids:

65% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Any loose, powdery or flaking paint should be removed with a wire brush. Fungus or mould should be scraped off and the surface treated with ATR131 Anti-Mould Wash. Previously unpainted or porous surfaces should be treated with EL56/70 Emulsion Sealer and allowed to dry thoroughly before coating with E57. Concrete surfaces should be treated with RL10/70/1 Chlorinated Rubber Sealer or AS56/5 Alkali Resisting Sealer White before application of E57.

Application:

By brush, roller or airless spray. Thin up to 10% by volume with water for brushing, or up to 20% by volume with water for spraying. On rough or porous surfaces, two coats may be required and it is recommended that the first coat is thinned up to 10% by volume for ease of application when brushing, allowing overnight drying between coats. E57 must be stirred thoroughly before and during use.

Coverage:

Approximately 20 - 30 sq metres per 5 Litres per coat, depending on porosity of surface.

Drying:

Touch dry: 6 - 8 hours @ 20°C.

Recoatable: Overnight.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.