



TECHNICAL PAINT SERVICES

RP1007 ACRYLATED RUBBER PRIMER

Features:

An anti-corrosive primer for use on clean wood or metal (ferrous) surfaces to add grip of subsequent, A1007 Acrylated Rubber System.

Availability:

5 Litre containers in Grey and Light Cream.

Volume Solids:

55 % +3% (BS 3900 Part A10).

Preparation:

Surface should be clean, dry and sound. For surfaces other than above please contact our technical department for guidance.

Application:

By brush, roller, conventional or airless spray. Thin as required using UTR112 Thinners. We recommend a 1.9 Thou' airless tip size at 2000psi.

Coverage:

Approximately 40 - 50 metres per 5 Litres depending on the surface profile.

Drying:

Touch dry: 1/2 hour @ 20°C.

Recoatible: 8 hours.

Fully cured: 24 hours.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 0845 230 1244 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.com

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.