

TECHNICAL PAINT SERVICES

The Paint Centre,
27 Southcote Road,
Bournemouth, Dorset, BH1 3SH.
T: 0845 230 1244 F: 0845 230 1255 E: enquiries@tecpaints.com
www.technicalpaintservices.com



Technical Paint Services

GRAFFITI MAGIC MATT & GLOSS

Product Information

Description

- A unique one-pack, white spirit based, external coating designed to give effective protection against both graffiti and fly-poster attack and is a semi-transparent/clear liquid
- Graffiti Magic is a permanent not a sacrificial system, allowing for repeated easy removal of any graffiti.
- Graffiti Magic is available in matt or gloss finish and has been specifically designed to minimise any alteration to the appearance of the protected surface.

Suitable Substrates

- Graffiti Magic is suitable for a wide variety of surfaces.
- The matt version is particularly effective on the normally difficult to protect substrates such as rough brick or textured finishes.
- Graffiti Magic can be used on concrete, render, masonry, porous stone, timber and previously painted surfaces. **(USE WITH MASONRY PAINTS SHOULD BE TESTED FIRST FOR ADHESION. A SMALL AREA SHOULD BE TESTED FIRST). TECHNICAL PAINT SERVICES CANNOT BE HELD RESPONSIBLE FOR PROBLEMS CAUSED WITHOUT TESTING.**
- **It should not be used over pliolite based products without first applying to a test area.**
- **To test the suitability of Graffiti Magic we recommend a small trial application be carried out or contact our technical department who will be pleased to give advice.**

Other Data

- Spread rate: 8 square metres; less on a porous substrate.
- The drying time: 1 – 3 hours, depending on conditions.
- Re-coat interval: between 2 and 4 hours.
- Application temperature: minimum 5°C.
- Working time: approximately 30 to 90 minutes. Due to the moisture curing nature of the product do not leave in opened containers.
- Equipment: take care to clean equipment immediately after use, however some rollers and brushes may need to be disposed of.
- Shelf Life: 12 months in unopened container.
- UV Resistance: Excellent.

Application

- Stir contents thoroughly before application.
- Apply two coats of Graffiti Magic at the suggested spread rate to obtain optimum results, by brush, roller or spray. If spraying, take care to avoid overspray as this may damage surrounding property.
- Porous surfaces should be sealed with Graffiti Magic Non Darkening Sealer which also acts as a non darkening sealer on substrates that will darken when coated directly with Graffiti Magic.