



# TECHNICAL PAINT SERVICES

## WB1011 ACRYLIC CONCRETE COATING

**Features:**

A water based semi recycled acrylic emulsion, specially formulated for coating onto concrete, brick, plaster, and some natural stone ornaments.

**Availability:**

To order in bulk only.

**Volume Solids:**

45% ± 3% (BS 3900 Part A10).

**Preparation:**

The surface should be well cleaned and all algae removed with a fungicidal wash and completely dry before coating. All untreated or new surfaces should be coated with a coat of primer prior to coloured top coats being applied.

**Application:**

By brush only. Supplied ready for brushing. For your own safety when applying, insure that gloves and eye protection are worn at all times. Do not apply in damp or wet conditions or when rain is likely to fall within 24 hours. Do not apply below 10°C or onto a very cold surface. Use clean tap water for cleaning of all equipment.

**Coverage:**

Determined by particle size and colour.

**Drying:**

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.