



# TECHNICAL PAINT SERVICES

## WB1012 SAIL DRESSING

**Features:**

A water based 100% pure acrylic emulsion, specifically made to re-colour and preserve canvas sails.

**Availability:**

Red Ochre and White. In 5 Litre containers.

**Volume Solids:**

45% ± 3% (BS 3900 Part A10).

**Preparation:**

The surface should be thoroughly clean, dry and free from dust and grease. Previously painted surfaces should be wetted down and dried.

**Application:**

Brush, Roller, Conventional or Airless spray. Supplied ready for use for brushing or roller. Use clean tap water for thinning, if required, and cleaning. It is recommended that two coats be applied to previously treated surfaces, allowing 2 hours drying between coats. For new and untreated surfaces you should apply one thinned coat with 20% clean tap water followed by two full coats allowing a minimum of 2 hours between coats.

**Coverage:**

Approximately 50 sq metres per 5 Litres, depending on porosity of substrate.

**Drying:**

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.  
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.