



TECHNICAL PAINT SERVICES

WB182 ACRYLIC WOOD PRIMER UNDERCOAT

Features:

A high performance primer/undercoat specially formulated on a water thinable emulsion resin. Suitable for interior or exterior application. WB182 Acrylic Wood Primer Undercoat has been designed to drastically reduce the expensive recoating time factor that is so important to the decorator and painting contractor. Suitable for use on most non-metal surfaces such as timber, plaster, hardboard, building boards, cement and brickwork after suitable preparation. Ideal for factory priming of joinery.

Availability:

5 Litre containers. Off-White.

Volume Solids:

70% ± 3% (BS 3900 Part A10).

Preparation:

Surfaces must be sound, clean, dry and free from wax, grease and oil. Remove all dust and loose particles. On existing painted surfaces, remove all loose and flaking paint, and thoroughly rub down with abrasive paper. Any bare surfaces should be primed with a first coat.

Application:

Stir thoroughly and check colour before use. Apply by brush, medium or short piled roller or spray. Ensure adequate ventilation during application and drying. Do not apply at temperatures below 8°C or when raining or foggy.

Coverage:

Approximately 11 - 13 sq metres per Litre depending on porosity of substrate.

Drying:

Normally 1 hour @ 18°C and 65% humidity. Recoatable within 2 hours enabling the second coat to be applied to fulfil the function of an undercoat. After a further 2 hours, the final gloss coat can be applied enabling a three coat painting system to be completed in one day.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.